

# FABRITRAK SYSTEMS, INC. FIRE TEST REPORT

**SCOPE OF WORK**

ASTM E84 TESTING ON POLYESTER INFILL

**REPORT NUMBER**

H5200.01-121-24

**TEST DATE**

08/31/17

**ISSUE DATE**

09/20/17

**RECORD RETENTION END DATE**

08/31/21

**PAGES**


9

**DOCUMENT CONTROL NUMBER**

ATI 00537 (07/24/17)

RT-R-AMER-Test-2780

© 2017 INTERTEK



## TEST REPORT FOR FABRITRAK SYSTEMS, INC.

Report No.: H5200.01-121-24

Date: 09/20/17

### REPORT ISSUED TO

**FabriTrak Systems, Inc.**

111 West Park Drive

Mt. Laurel, New Jersey 08054

### SECTION 1

#### SCOPE

Intertek Building & Construction (B&C) was contracted by FabriTrak Systems, Inc., Mt. Laurel, New Jersey to evaluate the flame spread and smoke developed properties of polyester infill. Testing was conducted at the Intertek B&C test facility in York, Pennsylvania. Results obtained are tested values and were secured by using the designated test method(s). A summary of test results and the complete graphical test data is reported herein.

This report does not constitute certification of this product nor an opinion or endorsement by this laboratory.

### SECTION 2

#### SUMMARY OF TEST RESULTS

**Product Type:** Polyester Infill

**Series/Model:** Terra Core Poly B™

#### ASTM E84 Test Results

FLAME SPREAD INDEX	SMOKE DEVELOPED INDEX
0	120

For INTERTEK B&C:

<b>COMPLETED BY:</b>	Ben Samson	<b>REVIEWED BY:</b>	Ethan Grove
<b>TITLE:</b>	Technician – Fire Testing	<b>TITLE:</b>	Manager – Fire Testing
<b>SIGNATURE:</b>		<b>SIGNATURE:</b>	
<b>DATE:</b>	09/20/17	<b>DATE:</b>	09/20/17

BTS:ddr

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample(s) tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

## TEST REPORT FOR FABRITRAK SYSTEMS, INC.

Report No.: H5200.01-121-24

Date: 09/20/17

### SECTION 3

#### TEST METHOD

The specimens were evaluated in accordance with the following:

**ASTM E84-16**, *Standard Test Method for Surface Burning Characteristics of Building Materials*

### SECTION 4

#### MATERIAL SOURCE/INSTALLATION

Test samples were provided by the client.

### SECTION 5

#### LIST OF OFFICIAL OBSERVERS

NAME	COMPANY
Ben Samson	Intertek B&C
Tim Feltman	Intertek B&C

### SECTION 6

#### TEST PROCEDURE

The Steiner Tunnel test apparatus is used to evaluate the surface burning characteristics and smoke development of building materials. The apparatus is considered to be under calibrated conditions when the flame front reaches the end of the tunnel within 5 minutes and 30 seconds (plus or minus 15 seconds) during a red oak test. An initial preheat of the tunnel is performed and the test specimen is installed when the tunnel temperature drops to 105°F ± 5°F. When the test is initiated, the 88 KW dual burner and 240 feet per minute air current creates a flame that extends 4.5 feet down the tunnel. The flame progression is tracked from this point to the exhaust end of the tunnel which is 19.5 feet downstream. An observer simultaneously notes any test specimen anomalies such as melting, dripping, sagging, delamination, fall-out, etc. The smoke that is generated during the test is measured by a photometer. The flame spread and smoke developed data are automatically logged and graphed versus time by a data acquisition and computer system. The Flame Spread Index (FSI) and the Smoke Developed Index (SDI) are based on an area under the curve calculation and the red oak flooring calibration data.

**TEST REPORT FOR FABRITRAK SYSTEMS, INC.**

Report No.: H5200.01-121-24

Date: 09/20/17

**SECTION 7**

**TEST SPECIMEN DESCRIPTION**

<b>MANUFACTURER*</b>	FabriTrak Systems, Inc.
<b>PRODUCT TYPE*</b>	Polyester Infill
<b>SERIES/MODEL*</b>	Terra Core Poly B™
<b>COMPOSITION*</b>	100% Polyester
<b>CONDITIONING TIME</b>	48 hr.
<b>SPECIMEN SIZE</b>	23-1/2 in. wide 47-1/2 in. long
<b>THICKNESS</b>	1 in.
<b>SPECIMEN SECTIONS</b>	6
<b>TOTAL WEIGHT</b>	1.6 lbs.
<b>COLOR</b>	White
<b>SIDE TO FLAME*</b>	Non-labelled side
<b>SUPPORT USED*</b>	Material was self-supporting
<b>MOUNTING METHOD</b>	Material was self-supporting
<b>SUBSTRATE USED*</b>	No substrate was utilized
<b>CEMENT BOARD</b>	1/4 in. thick fiber cement board was placed on top of the sample.

\*From the client's material description and/or instructions

**Note:** Specimens were conditioned as per the requirements of Section 6.4 of ASTM E84.

**SECTION 8**

**CODES AND REGULATIONS**

The 2015 International Building Code® (Chapter 8 Interior Finishes, Section 803 Wall and Ceiling Finishes) and NFPA 5000, (Chapter 10 Interior Wall or Ceiling Finish Testing and Classification) classify materials based on their Flame Spread and Smoke Developed indices. The classification criteria are listed below:

<b>CLASSIFICATION</b>	<b>FLAME SPREAD INDEX</b>	<b>SMOKE DEVELOPED INDEX</b>
A	0-25	0-450
B	26-75	0-450
C	76-200	0-450

**TEST REPORT FOR FABRITRAK SYSTEMS, INC.**

Report No.: H5200.01-121-24

Date: 09/20/17

**SECTION 9****TEST RESULTS**

<b>TEST RESULTS</b>	
Test Date	08/31/17
Test Operator	Ben Samson
Flame Spread Index (FSI)	0
Smoke Developed Index (SDI)	120
Red Oak Calibration (% * Min)	101.62

<b>TEST DATA</b>	
FSI (unrounded)	0.0
SDI (unrounded)	120.6
FS * Time Area (Ft * Min)	0.0
Smoke Area (% * Min)	122.5
Fuel Area (°F * Min)	4970.7

<b>OBSERVATIONS</b>	
Ignition Time	00:09(Min:Sec)
Max Flame Front Advance	0.0 Feet
Time to Max Flame Front	00:00(Min:Sec)
Max Temp At Exposed T/C	603.8°F
Time To Max Temp	09:57(Min:Sec)
Dripping Observed	00:10(Min:Sec)
Flaming On Floor Observed	05:23(Min:Sec)
After Flame Top Observed	None
After Flame Floor Observed	10:03(Min:Sec)
Sagging Observed	None
Delamination Observed	None
Shrinkage Observed	None
Fallout Observed	None
Cracking Observed	None
Observations After the Test	None

## TEST REPORT FOR FABRITRAK SYSTEMS, INC.

Report No.: H5200.01-121-24

Date: 09/20/17

### SECTION 10 PHOTOGRAPHS



**Photo No. 1**  
**Exposed Surface of the Test Specimen (Pre-test)**



**Photo No. 2**  
**Unexposed Surface of the Test Specimen (Pre-test)**

## TEST REPORT FOR FABRITRAK SYSTEMS, INC.

Report No.: H5200.01-121-24

Date: 09/20/17

### SECTION 8 (Continued) PHOTOGRAPHS



**Photo No. 3**  
**Unexposed Surface of the Test Specimen (Post-test)**

## TEST REPORT FOR FABRITRAK SYSTEMS, INC.


Report No.: H5200.01-121-24

Date: 09/20/17


### SECTION 9

#### GRAPHS


Flame Spread



Smoke Developed



Temperature







Total Quality. Assured.

130 Derry Court  
York, Pennsylvania 17406

Telephone: 717-764-7700  
Facsimile: 717-764-4129  
[www.intertek.com/building](http://www.intertek.com/building)

**TEST REPORT FOR FABRITRAK SYSTEMS, INC.**

Report No.: H5200.01-121-24

Date: 09/20/17

**SECTION 10**

**REVISION LOG**

REVISION #	DATE	PAGES	REVISION
0	09/20/17	N/A	Original Report Issue